

tapes





IP YOUR BIG BAGS GET EXPOSED TO THE ELEMENTS ...

UV STABILISATION OF PP TAPES



WHAT YOU NEED TO KNOW ABOUT SOLAR RADIATION

Good UV stabilisation of a PP tape should ensure that at least 50% of the initial tensile strength is present in the woven fabric at the end of its desired service life. It is important to note that each type of UV stabilisation must be designed to withstand the maximum possible annual solar radiation that typically occurs in the geographic location where the final product is used. The solar radiation depends on climatic factors and can vary widely according to the place of exposure.





GLOBAL RADIATION MAP





It is therefore vitally important to design a light stabiliser for PP tapes to suit the geographical area in which the final product will be used.

Our product recommendations are based upon solar radiation according to place of exposure in the form of kLy/year - units. Reductive chemical influences from the atmosphere or from contact with chemicals, and the addition or deteriorating dyes or additives to the polymer - whether intentional or not - must always be considered and require specific testing before product recommendations are made.

THE FOLLOWING SOLAR RADIATION VALUES CAN BE CONSIDERED NORMAL

The solar radiation energy is usually expressed in kLy (Kilolangely) units. A conversion to other energy units is possible as follows:

A conversion to other energy units is possible as follows.		
1 kLy = 1000 Ly (Langely)	AREA	KLY
1 kLy = 4187.5 J/cm ² = 4.19 kJ/cm ²	Scandinavia	60-80
1 kLy = 11.62 kWh/m ²	Central Europe	100-120
	Southern Europe	120-160
	Northern Africa	160-180
	Northern Russia	80
	Southern Russia	140
	Δustralia	180-200

SEVEN WORLD CLIMATES 2_POLAR

6_HUMID MICRO THERMAL

I_DRY DESERT

ARTIFICIAL WEATH

THE RADIATION SPECTRA

RANGE	WAVELENGTH	% OF LIGHT
UV-C	< 280 nm	0
UV-B	280-320 nm	0.5
UVA-A	320-400 nm	5.6
VIS - visible	400-800 nm	
IR-A	800-1400 nm	29.4
IR-B	1400-3000 nm	12.7
IR-C	> 3000 nm	"Negligible for testing"

SPECTRAL SENSITIVITIES OF POLYMERS

PE	300-310, 340
PP	290-300, 330, 370
PS	320-325
PA	290-315
PC	280-310
SAN	310-330, 290
ABS	300-310, 370-385
PMMA	290-315

All indications in nanometre wavelengths Literature: ATLAS MTS



5_HUMID MESO THERMAL



ERiNG

SUNLIGHT VS. FLUORESCENT UV LAMP

Fluorescent UV lamps simulate narrow UV radiation under specific conditions. They do not cause heating effects through visible or infrared light. A comparison with service life performance or a correlation with outdoor exposure is not possible.

and the state of the

TROPICAL



Literature: ATLAS MTS

WAVELENGTH (NANOMETRES)

WHICH INFLUENCES CAN DEGRADE THE UV STABILISATION OF PP TAPES

THE SERVICE LIFE OF UV-STABILISED PPTAPES IS SIGNIFICANTLY

INFLUENCED by the quality of the polymer (or polymer blends) to be stabilised. Once selected, polymers should not be changed. New polymers should be carefully evaluated in tests for whether they can degrade the light stabilisation - the same procedure is recommended if new additives are used.

APART FROM OTHER CRITERIA, THE WALL THICKNESS OF THE TAPES

to be stabilised is especially critical to the design of a UV stabiliser. Extreme weakening of the wall thickness through extreme stretching leads to significant shortening of the tapes' expected service life.

PIGMENTATION CAN IMPROVE OR DEGRADE THE UV STABILITY of a

UV-stabilised polymer. In our combination Colour/UV Stabiliser products, we only use compatible pigments which have proven their performance on the basis of long-term experience.

SOME CONTACT MEDIA (such as agro-chemicals) can decrease the UV performance of tapes. In particular, additives containing sulphur, flame retardants containing acid-splitting halogen and critical packaging contents that come into direct contact with the tapes can lead to significant degradation of the UV stabilisation.

POOR CUTTING QUALITY OF TAPES USING BLADES with too much abrasive wear will cause oxidation and degradation of the polymer during exposure and increase the vulnerability of the tapes. This can further degrade good light stabilisation.

CALCIUM CARBONATE (CACO₃) IS FREQUENTLY USED IN

MASTERBATCH as an antisplit additive in the production of PP tapes due to the better weaving properties it offers. It must be noted that specific impurities in some CaCO₃ grades will cause considerable degradation of UV stabilisation. Selection of a CaCO₃ masterbatch with a highly pure CaCO₃ grade as used in our MAXITHEN® PP7A7120ASP Antisplit MB is very important.

IT MUST BE CONSIDERED THAT DARK COLOURS absorb more thermal energy during outdoor exposure, which speeds up the heat-related ageing process of the polymer itself; increased addition of light stabiliser may be necessary if such colours are used.

PP TAPE RANGE



SiNGLE MASTERBATCH

- _ UV STABILISATION
- _ ASP ANTISPLIT
- _ AS ANTISTATIC
- _ AO ANTIOXIDANT
- _ FR FLAME RETARDANT
- _ WHITE
- _ BLACK



COMBINATION MASTERBATCH



ALL IN ONE MASTERBATCH

_ UV+ASP+WHITE

Further products on request

_ UV+ASP

_ ASP+WHITE

Tailor-made combinations possible



SiNGLE MASTERBATCH

UV PROTECTION

PP7AA1570UV: High-efficiency HALS stabiliser, especially suitable for polypropylene, on PP carrier, for best price/performance ratio. Standard grade for PP tape fabrics for industrial packaging and technical applications

PP7AA1570/11UV: Lower concentration of standard grade PP7AA1570UV, recommended when the required service life/dosage rate of PP7AA1570UV would be too low for proper distribution of the active ingredient in the polymer melt

PP72200UV: High-efficiency oligomeric HALS stabilisers, on PP carrier, for best price/performance ratio. Standard grade for PP tape fabrics, suitable for food contact

PP7AA7380/11UV: Lower concentration of standard grade PP7AA7380UV, recommended when the required service life/dosage rate of PP7AA7380UV would be too low for proper distribution of the active ingredient in the polymer melt. For PP tape fabrics, suitable for food contact

PP7AA7460UV: High-efficiency oligomeric HALS stabiliser, especially suitable for polypropylene, combined with absorber for synergistic effects to further increase UV protection of packed goods, on PP carrier. For PP tape fabrics, suitable for food contact

PP791360UVFR: Special grade for high UV stabilisation performance combined with flame retardancy, halogen free, on PP carrier. For PP tape fabrics



ANTISPLIT

PP7A7120ASP: High loaded (80%) selected high purity Antisplit Calcium Carbonate grade of low abrasivity on PP carrier. Offers smooth tape surface for good and dustless weaving process. For polypropylene tape fabrics, suitable for food contact

ANTISTATICS

PP791310AS: Fast and efficiant antistatic agent, migrating, on PP carrier, suitable for food contact

UNS7A4420AS: Polymeric permanent antistatic agent with immediate effect, non migrating. For fabrics made from polyethylene and polypropylene, suitable for food contact

ANTIOXIDANTS

PP792210AO: Synergistic combination of process and longterm heat stabiliser, on PP carrier. For all types of woven fabrics made from polypropylene, suitable for food contact

FLAME RETARDANTS

PP7A8150FR: High-performance flame retardant, low halogen content, compatible with HALS UV stabilisers, on PP carrier. For all types of woven fabrics made from polypropylene

PP7AA1940UVFR: High-performance flame retardant, halogen free, compatible with HALS UV stabilisers, on PP carrier. For all types of woven fabrics out of polypropylene

WHITE & BLACK, COLOURS

PP1131/70WHITE: High loaded (70%) weather resistant and HALS compatible TiO₂ pigment on PP carrier, **suitable for food contact**

HP1139/60, HP1139/70WHITE: High loaded (60%/70%) weather resistant and HALS compatible TiO₂ pigment on PE carrier. For tapes made from polyethylene and polypropylene, suitable for food contact

HP99611BLACK: High colour strength UV protection carbon black, good dispersion, excellent compatibility with HALS UV stabilisers. On PE carrier, for tapes made from polyethylene and polypropylene, suitable for food contact (EU)

HP98781BLACK: High colour strength UV protection carbon black, good dispersion, excellent compatibility with HALS UV stabilisers. On PE carrier, for tapes made from polyethylene and polypropylene, suitable for food contact (EU & FDA)

Tailor-made formulations in each colour shade available upon request.



MULTIFUNCTIONAL COMBINATION MASTERBATCH

UV PROTECTION + ANTISPLIT

PP7AA5540UVASP: High-efficiency HALS stabiliser, especially suitable for polypropylene, combined with selected high purity Antisplit Calcium Carbonate grade of low abrasivity, on PP carrier, for best price/performance ratio. Standard grade for PP tape fabrics for industrial packaging and technical applications

PP7AA5540/11UVASP: Lower concentration of standard grade PP7AA5540UVASP, recommended when the required service life/dosage rate of PP7AA5540UVASP would be too low for proper distribution of the active ingredient in the polymer melt

PP7AA7390UVASP: High-efficiency oligomeric HALS stabilisers combined with selected high purity Antisplit Calcium Carbonate grade of low abrasivity, on PP carrier, for best price/performance ratio. Standard grade for PP tape fabrics, suitable for food contact

PP7AA7390/11UVASP: Lower concentration of standard grade PP7AA7390UVASP, recommended when the required service life/dosage rate of PP7AA7390UVASP would be too low for proper distribution of the active ingredient in the polymer melt. For PP tape fabrics, suitable for food contact

PP1AA4541ASPWHITE: All-in-one formulation of selected high purity Antisplit Calcium Carbonate grade of low abrasivity, combined with weather resistant, HALS compatible TiO₂ pigment, on PP carrier. Offers correct proportion of functional ingredient and white colour at favourable price level, no risk of wrong dosage and mix-ups in contrast with use of single components. For PP tape fabrics, suitable for food contact



ALL IN ONE

PP1AA4531UVASPWHITE: All-in-one formulation of high-efficiency HALS stabiliser, especially suitable for polypropylene, combined with selected high purity Antisplit Calcium Carbonate grade of low abrasivity, and with weather resistant, HALS compatible TiO₂ pigment, on PP carrier. Offers correct proportion of functional ingredients and white colour at favourable price level, no risk of wrong dosage and mix-ups in contrast with use of single components. Tailor-made solutions also available on request

PP1AA3671UVASPWHITE: All-in-one formulation of high-efficiency HALS stabiliser, especially suitable for polypropylene, combined with selected high purity Antisplit Calcium Carbonate grade of low abrasivity, and with weather resistant, HALS compatible TiO₂ pigment, on PP carrier. Offers correct proportion of functional ingredients and white colour at favourable price level, no risk of wrong dosage and mix-ups in contrast with use of single components. Tailor-made solutions also available on request, suitable for food contact

MISCELLANEOUS MASTERBATCH

Antimicrobials, temperature & light exposure indicators, on-line-control for wall thickness and masterbatch dosage, counterfeit protection on request/under development

ALSO FOR HIGH-VALUE GOODS



SLIP, POLYMER PROCESSING AID, ANTIBLOCK & COMBINATIONS

HP7051E: High-performance Erucamide slip agent, on PE carrier. Standard grade for all types of PE film, suitable for food contact

HP7A8770PPA: High-performance Polymer Processing Aid for improved processability of Polyolefines. Offers smooth surface of the films, less energy consumption of extrusion lines, reduces dye build-ups. On PE carrier, for all types of PE film, suitable for food contact

HP7011/65AB: Natural Silica Antiblock, on PE carrier. For all types of PE film, suitable for food contact

HP7081ABGLE: High-performance Erucamide slip agent combined with natural Silica Antiblock, on PE carrier. Standard grade for all types of PE film, suitable for food contact

HP7AA7180ABGLE: High-performance Erucamide slip agent combined with natural Silica Antiblock and Calcium Carbonate, on PE carrier. For all types of PE film, suitable for food contact

UV PROTECTION

HP79860UV: High-efficiency oligomeric HALS stabiliser on PE carrier for best price/performance ratio, standard grade for PE Blown & Cast film and tapes, suitable for food contact

ANTISTATICS

HP7041/05AS: Amine-based migrating antistatic agent on PE carrier, good price/ performance ratio, suitable for food contact

HP77571AS: Amide-based migrating Antistatic agent on PE carrier, good price/ performance ratio, non-corrosive, **suitable for food contact**

UNS7A4420AS: Polymeric permanent antistatic with immediate effect, non migrating. For all polyolefines, suitable for food contact



FLAME RETARDANTS

HP73940FR: Halogenated flame retardant with good price/performance ratio, on PE carrier, for industrial packaging films

HP7AA1460FR: Halogen-free flame retardant, on PE carrier, for industrial packaging films

HP791460UVFR: Special grade for high UV stabilisation performance combined with flame retardancy, halogen-free, on PE carrier, for industrial packaging films

WHITE & BLACK, COLOURS

HP13301WHITE: 70% TiO₂ pigment for indoor use, on PE carrier. For films of >60 μ made from polyethylene and polypropylene, suitable for food contact

HP17201WHITE: 60% TiO₂ pigment for indoor use and 15% high purity chalck. For films of >60 μ out of Polyethylene and Polypropylene, suitable for food contact

HP100221WHITE: 25% TiO₂ pigment for indoor use and 50% high purity chalck. For films of >60 μ made from polyethylene and polypropylene, suitable for food contact

HP19201/HP19301WHITE: 60/70% TiO₂ pigment for indoor use. For multilayer films of >5 µ/layer, made from polyethylene and polypropylene. Low lacing grade formulation, suitable for food contact

HP99611BLACK: High colour strength UV protection carbon black, good dispersion, excellent compatibility with HALS UV stabilisers. On PE carrier, for tapes made from polyethylene and polypropylene, suitable for food contact (EU)

HP98211BLACK: High colour strength carbon black for indoor application, good dispersion. On PE carrier, for tapes of >40µ made from polyethylene and polypropylene, for industrial packaging

Tailor-made formulations in each colour shade available upon request

MISCELLANEOUS

Temperature & light exposure indicators, on-line-control for wall thickness and masterbatch dosage, counterfeit protection on request/under development

BUSINESS UNITS OF GABRIEL-CHEMIE GROUP:



schaft m. b. H. - All images in this folder are symbolic photos for illustration hown are not necessarily produced with masterbatches of Gabriel-Chemie.

© 2016 GABRIEL-CHEN urposes only, the final p





Packaging for Industrial & Consumer Goods









GABRIEL-CHEMIE Gesellschaft m. b. H. Industriestraße 1 2352 Gumpoldskirchen AUSTRIA Tel. +43 2252 636 300 Fax +43 2252 627 250 info@gabriel-chemie.com

WWW.GABRIEL-CHEMIE.COM